

01.07.2019


Rebar coupler HBS Raccordo filettato HBS

HBS-M

Standard threaded sleeve, pre-mounted inc. locking screw.
Suitable for standard HBS screw thread.

Manicotto filettato standard, premontato con vite di chiusura
Adatto per filettatura standard HBS

Bar reference Denominazione della barra $\varnothing d_s$	Dimensions Dimensioni					
	Screw thread Filettatura		L1 mm	LM mm	SW mm	E mm
HBS-M-12	ISO	M 12 x 1,75	16	36	19	21,9
HBS-M-14	ISO	M 14 x 2	19	42	22	25,4
HBS-M-16	ISO	M 16 x 2	22	48	24	27,7
HBS-M-18	ISO	M 18 x 2,5	26	56	27	31,2
HBS-M-20	ISO	M 20 x 2,5	28	60	30	34,6
HBS-M-22	ISO	M 22 x 2,5	31	68	32	37,0
HBS-M-26	ISO	M 27 x 3	33	75	41	47,3
HBS-M-30	ISO	M 30 x 3,5	43	90	46	53,1
HBS-M-34	Spéc./Spez.	M 34 x 3	50	105	50	57,7
HBS-M-40	Spéc./Spez.	M 40 x 4	60	130	60	69,3



Symbol / simbolo




HBS-R

Standard threaded sleeve suitable for standard HBS-M
screw thread with thread protection.

Filettatura standard adatta per manicotto HBS
standard HBS-M con protezione della filettatura

Bar reference Denominazione della barra $\varnothing d_s$	Dimensions Dimensioni		
	Screw thread Filettatura		L3 mm
HBS-R-12	ISO	M 12 x 1,75	16
HBS-R-14	ISO	M 14 x 2	19
HBS-R-16	ISO	M 16 x 2	22
HBS-R-18	ISO	M 18 x 2,5	26
HBS-R-20	ISO	M 20 x 2,5	28
HBS-R-22	ISO	M 22 x 2,5	31
HBS-R-26	ISO	M 27 x 3	33
HBS-R-30	ISO	M 30 x 3,5	43
HBS-R-34	Spéc./Spez.	M 34 x 3	50
HBS-R-40	Spéc./Spez.	M 40 x 4	60



Symbol / simbolo




HBS-S

Welding coupler HBS-S suitable for the standard HBS thread

Manicotto a saldare, adatto per la filettatura standard HBS

Bar reference Denominazione della barra $\varnothing d_s$	Dimensions Dimensioni					
	Screw thread Filettatura		L mm	D mm	B mm	H mm
HBS-S-12	ISO	M 12 x 1,75	24	32	3.70	3.40
HBS-S-14	ISO	M 14 x 2	27	32	3.70	3.40
HBS-S-16	ISO	M 16 x 2	30	32	3.70	3.40
HBS-S-18	ISO	M 18 x 2,5	33	32	4.20	3.90
HBS-S-20	ISO	M 20 x 2,5	36	36	5.20	4.90
HBS-S-22	ISO	M 22 x 2,5	38	40	5.60	5.30
HBS-S-26	ISO	M 27 x 3	45	45	7.00	6.60
HBS-S-30	ISO	M 30 x 3,5	54	57	7.70	7.30
HBS-S-34	Spéc./Spez.	M 34 x 3	58	60	8.80	8.20
HBS-S-40	Spéc./Spez.	M 40 x 4	68	70	9.50	8.90



Symbol / simbolo




HBS-RDZ

Reducing coupler, pre-mounted inc. locking screw

Suitable for the standard HBS thread

Manicotto riduttore, premontato con vite di chiusura
Adatto per filettatura standard HBS

Bar reference Denominazione della barra $\varnothing d_s$	Dimensions Dimensioni					
	Screw thread Filettatura		LIR [mm]	Lmrdz [mm]	SW [mm]	A [mm]
HBS-RDZ-16/12	M16x2	/ M12x1,75	23	48	24	27.7
HBS-RDZ-16/14	M16x2	/ M14x2	23	48	24	27.7
HBS-RDZ-18/14	M18x2,5	/ M14x2	27	56	27	31.2
HBS-RDZ-18/16	M18x2,5	/ M16x2	27	56	27	31.2
HBS-RDZ-20/16	M20x2,5	/ M16x2	29	60	30	34.6
HBS-RDZ-20/18	M20x2,5	/ M18x2,5	29	60	30	34.6
HBS-RDZ-22/18	M22x2,5	/ M18x2,5	34	68	32	37.0
HBS-RDZ-22/20	M22x2,5	/ M20x2,5	34	68	32	37.0
HBS-RDZ-26/20	M27x3	/ M20x2,5	39	75	41	47.3
HBS-RDZ-26/22	M27x3	/ M22x2,5	39	75	41	47.3
HBS-RDZ-30/22	M30x3,5	/ M22x2,5	44	90	46	53.1
HBS-RDZ-30/26	M30x3,5	/ M27x3	44	90	46	53.1
HBS-RDZ-34/26	M34x3	/ M27x3	52	105	50	57.7
HBS-RDZ-34/30	M34x3	/ M30x3,5	52	105	50	57.7
HBS-RDZ-40/30	M40x4	/ M30x3,5	67	130	60	69.3
HBS-RDZ-40/34	M40x4	/ M34x3	67	130	60	69.3



Symbol / simbolo

